


PURBlue™ 4 Adhesive Melters



Nordson® PURBlue 4 adhesive melters simplify use of moisture-cure reactive (PUR) hot melt adhesives in two-, three- or four-kilogram foil encased slugs. The user-friendly design offers simple, reliable operation with quick disassembly for ease of cleaning and maintenance. The “melt-on-demand” process uses only the adhesive needed so reduces thermal stress and protects bonding characteristics of the unused PUR, which remains sealed in its foil bag. Adjustable force on the foil bag delivers optimal contact between adhesive and melting grid to minimize adhesive residue in empty bags. The ability to easily use small volumes of PUR helps increase productivity and reduce adhesive waste.

PURBlue 4 melters:

- Are easy to install and operate with no inert gas requirement
- Provide easy day-to-day operation and maintenance
- Utilize true melt-on-demand temperature control system
- Maximize adhesive usage and reduce residual waste
- Protect adhesive integrity
- Provide simple shutdown procedure for overnight or weekends





Flow-through output manifold with no dead spaces can accommodate up to three hoses



Foil-encased PUR slug

Specifications

Type of System	PUR slug melter with spur gear pump
Foil Bag Diameter	125 mm and 150 mm
Melt Rate (per hour)	4 kg/hr (9 lb/hr)
Holding Capacity	One slug plus 0.75 kg reservoir
Maximum Pump Rate	7.7 cc/rev.
Maximum Working Hydraulic Pressure	75 bar (1100 psi)
Temperature Sensor	Nickel RTD (Ni120)
Operating Temperature Range	40 to 175° C (100 to 350° F)
Ambient Temperature Range	0 to 50° C (32 to 122° F)
Viscosity Range	up to 50,000 cps
Electrical Service	200 VAC 1/3 phase 50/60 Hz 200 to 240 VAC 1/3 phase 50/60 Hz 380 to 415 VAC-Y (3 phase N/PE) 50/60 Hz
Maximum System Power Capacity	6000 watts
Input/Output Capability Standard	2 Std Inputs – programmable for function 3 Std Outputs – programmable for function Key-to-line
Number of Hose/Gun Pairs¹	3
Melter Dimensions (W x H x D)	685 x 964 x 382 mm (27 x 37.9 x 15 in)
Installation Dimensions (W x H x D)	1112 x 964 x 782 mm (43.8 x 37.9 x 30.8 in)
Approximate Weight (empty)	97 kg (214 lb)
Protection	IP32

¹ Standard Blue Series™ hoses and guns



For more information, talk with your Nordson representative or contact your Nordson regional office.

United States
Duluth, Georgia
Telephone: (800) 683-2314
Toll-free Facsimile:
(866) 667-3329

Canada
Markham, Ontario
Telephone: (800) 463-3200
Facsimile: (905) 475-8821

Europe
Lüneburg, Germany
Telephone: (49) 4131-894-0
Facsimile: (49) 4131-894-149

Japan
Tokyo, Japan
Telephone: (81) 3-5762-2700
Facsimile: (81) 3-5762-2701

**Asia/Australia/
Latin America**
Amherst, Ohio
Telephone: (440) 985-4797
Facsimile: (440) 985-1096

www.nordson.com



When you expect more.®