



Color-coded rings identify voltage and air flow to simplify solenoid replacement and troubleshooting.

Ring closest to coil identifies voltage

Ring furthest from coil identifies air flow (Cv value)

Air flow supports single and multi-module gun applications

applications



Saturn solenoids are designed specifically for Nordson pneumatic hot melt adhesive dispensing guns. These balanced, 3- and 4-way piloted valves deliver maximum shifting force in both directions by alternately supplying air to each end of the spool. Equal shifting forces at energization and de-energization result in resistance-free shifting, increased reliability and faster, more consistent response times.

Color-coded rings allow you to select the to correct replacement solenoid every time. Rings are a trademark of Nordson Corporation and are your assurance of genuine Nordson quality.

Saturn Solenoids are compatible with all Nordson pneumatic air-open/air-close (AO/AC) and air-open/spring-close (AO/SC) guns including new Classic Blue $^{\mathsf{TM}}$, SolidBlue $^{\mathsf{TM}}$ and SureBead $^{\mathsf{B}}$ guns.

Features and benefits

- Meets Nordson requirements for hot melt adhesive application, providing peak dispensing gun performance.
- Provides superior adhesive delivery with airflows of 1.0 Cv and 1.5 Cv for multi-module valves and .18 Cv for single module valves, resulting in improved cutoff.
- Improved valve life and reduced maintenance. High-temperature seals and components withstand temperatures in excess of 200° F (93° C).
- Eliminates guesswork and minimizes risk. Saturn solenoids are designed specifically for use with Nordson pneumatic hot melt dispensing guns.

Upgrading is easy

	Air-Open/Spr	ing-Close Gun, 3	-Way Solenoid Valv	ve		
Part Number	Connectors	Inner Ring - Voltage	Outer Ring - Air Flow (Cv)	Cv	Watts	Input Voltage
1062017	1/4 NPT, QD plug, LED light, MOV	Yellow	Green	1.5	5.4	24 VDC
1056119	1/4 NPT, QD plug, LED light	Yellow	Green	1.5	5.4	24 VDC
1055481	1/4 NPT, QD plug, no light	Yellow	Green	1.5	5.4	24 VDC
1056273	1/4 NPT, QD plug, no light	Red	Green	1.5	5.4	100 VAC
1056120	1/4 NPT, QD plug, no light	Beige	Green	1.5	5.4	120 VAC
1056274	1/4 NPT, QD plug, no light	Gold	Green	1.5	5.4	200 VAC
1056121	1/4 NPT, QD plug, no light	Grey	Green	1.5	5.4	240 VAC
1069208	1/8 NPT, QD plug, LED light	Yellow	White	.18	5.4	24 VDC
1069207	1/8 NPT, QD plug, no light	Yellow	White	.18	5.4	24 VDC
1069206	1/8 NPT, QD plug, no light	Green	White	.18	5.4	12 VDC
1069251	1/8 NPT, QD plug, no light	Blue	White	.18	5.4*	24 VAC
1069252	1/8 NPT, QD plug, no light	Brown	White	.18	5.2*	48 VAC
1069253	1/8 NPT, QD plug, no light	Red	White	.18	2.8*	100 VAC
1069254	1/8 NPT, QD plug, no light	Beige	White	.18	5.4*	120 VAC
1069255	1/8 NPT, QD plug, no light	Gold	White	.18	2.8*	200 VAC
1069256	1/8 NPT, QD plug, no light	Grey	White	.18	2.9*	240 VAC
	Air-Open/Ai	r-Close Gun, 4-V	Vay Solenoid Valve			
1055483	1/4 NPT, QD plug, LED light, MOV	Yellow	Blue	1.0	5.4	24 VDC
1053894	1/4 NPT, QD plug, LED light	Yellow	Blue	1.0	5.4	24 VDC
1055480	1/4 NPT, QD plug, no light	Yellow	Blue	1.0	5.4	24 VDC
1069250	1/8 NPT, QD plug, LED light	Yellow	White	.18	5.4	24 VDC
1069209	1/8 NPT, QD plug, no light	Yellow	White	.18	5.4	24 VDC
1069258	1/8 NPT, QD plug, no light	Grey	White	.18	2.9*	240 VAC
1069257	1/8 NPT, QD plug, no light	Beige	White	.18	2.8*	120 VAC

^{*} Rated Wattage of AC Solenoids at 60 Hz





For more information, talk with your Nordson representative or contact your Nordson regional office.

United States Canada Europe Japan Asia/Australia/ Duluth, Georgia Markham, Ontario Lüneburg, Germany **Latin America** Tokyo, Japan Telephone: (800) 683-2314 Telephone: (800) 463-3200 Telephone: (81) 3-5762-2700 Telephone: (49) 4131-894-0 Amherst, Ohio Facsimile: (866) 667-3329 Facsimile: (905) 475-8821 Facsimile: (49) 4131-894-149 Facsimile: (81) 3-5762-2701 Telephone: (440) 985-4797

Facsimile: (440) 985-1096

www.nordson.com



When you expect more.®