

# Why Choose Nordson?

Best Choice™ Hot Melt Dispensing Applicators



Feature	Why is this Important?	Nordson Best Choice Module	Competitor Module
Hydraulic seal material	Use of high-strength, high-lubricity seals ensures superior service life	Uses a Myritex™ seal composed of a proprietary blend of Teflon®, carbon and graphite	Seals made of Teflon only
Rebuild capability	The ability to rebuild modules saves time and reduces total cost of ownership.	Fully rebuildable	No feature
One-way installation	Fool-proof module alignment reduces installation time and aids in installing modules on difficult-to-reach applicators by ensuring one-handed, accurate alignment on applicator.	Uses the patented EasyOn™ mounting interface	No feature
Valve identification	Ability to correctly identify valve type and actuation method at a distance eliminates the need to access the parent machine to identify modules, ensuring consistent operation from valve-to-valve and applicator-to-applicator.	Standard color-coding	No feature
Protective covers	Protects personnel from incidental contact with hot surfaces	Uses patented heat-resistant plastic covers	No feature
Self-cleaning design	Virtually eliminates nozzle clogs	Available patented SureBead® technology cleans nozzle each cycle	No feature

For more information, talk with your Nordson representative or contact your Nordson regional office.

#### United States

Duluth, Georgia  
Telephone: 800.683.2314  
Facsimile: 866.667.3329

#### Canada

Markham, Ontario  
Telephone: 800.463.3200  
Facsimile: 905.475.8821

#### Europe

Erkrath, Germany  
Telephone: 49.211.9205.0  
Facsimile: 49.211.254.658

#### Japan

Tokyo, Japan  
Telephone: 81.3.5762.2710  
Facsimile: 81.3.5762.2717

#### Asia/Australia/Latin America

Amherst, Ohio  
Telephone: 440.985.4797  
Facsimile: 440.985.1096

[www.nordsonadhesive.com](http://www.nordsonadhesive.com)

PKL-17-5931  
Issued 1/17  
© 2017 Nordson Corporation  
All Rights Reserved.

Printed in U.S.A.  
Nordson reserves the right to  
make design changes between  
printings.

